

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A renal replacement therapy system, comprising:
 - a blood treatment device with at least one actuator peristaltic pump mechanism;
 - a cartridge with a fluid circuit supported thereby, the fluid circuit having respective portions to engage said at least one actuator peristaltic pump mechanism;
 - said blood treatment device including separate engagement elements ~~that~~, which are movable relative to each other to be brought together around said respective portions to engage said fluid circuit portions by forcing a first of said engagement elements against a second of said engagement elements, at least one of the engagement elements carrying the actuator peristaltic pump mechanism;
 - the blood treatment device including having a support member configured to extend between the engagement elements, with a first end portion attached to one of the engagement elements and a second end portion attached to the other engagement element, and further configured to permit the cartridge to rest thereon, wherein the support member is such that a vertical motion to rest the cartridge on the support member followed by a horizontal motion to engage the cartridge with an alignment member positions the cartridge such that the engagement elements are brought together around the respective portions to engage the at least one actuator and an alignment member shaped to align the eartridge with the at least one peristaltic pump mechanism when the eartridge is moved horizontally toward the alignment member, the support and alignment member being such

that a single vertical motion to rest the cartridge on the support followed by a single horizontal motion of the cartridge to engage the alignment member positions the cartridge such that the separate engagement elements may be brought together around the respective portions to engage the at least one peristaltic pump mechanism.

2. (Original) A system according to claim 1, wherein said fluid circuit includes an extracorporeal blood circuit.

3. (Original) A system as in claim 1, wherein said fluid circuit is configured for circulating blood from an individual through the blood treatment device to remove waste and to return blood and replacement fluid to the individual after removal of waste and said respective portions include a first portion for conveying waste, a second portion for conveying blood, and a third portion for conveying replacement fluid.

4. (Original) A system as in claim 1, wherein said at least one actuator includes a peristaltic pump with a single rotating element that pumps blood through multiple ones of said respective portions, said respective portions carrying different fluids including at least blood and another fluid.

5. (Original) A system as in claim 4, wherein said at least another fluid includes replacement fluid.

6. (Original) A system as in claim 4, wherein said at least another fluid includes waste fluid.

7. (Original) A system as in claim 1, wherein said first of said engagement elements includes a filter.

8. (Original) A system as in claim 1, wherein said first of said engagement elements is permanently attached to said fluid circuit forming a sterile consumable component which is replaced after a fixed number of treatments.

9. (Currently Amended) A method of performing renal replacement therapy using a blood treatment device with at least one actuator peristaltic pump mechanism carried by at least one of two separate engagement elements and a fluid circuit with respective portions to engage said at least one actuator peristaltic pump mechanism, comprising the steps of:

locating said fluid circuit respective portions on a support member, the support member being configured to extend between said separate engagement elements such that a first end portion of the support member is attached to one of the engagement elements and a second end portion is attached to the other engagement element between said separate engagement elements;

moving at least one of said engagement elements toward the other on the support member to bring them together such that the engagement elements squeeze said respective portions therebetween;

operating a pump in one of said engagement portions to convey at least blood and at least one other fluid in order to perform a therapeutic treatment.

10. (Original) A method as in claim 9, wherein said respective portions include fluid lines and said step of locating includes laying said fluid lines on a peristaltic pump.

11. (Original) A method as in claim 9, further comprising disposing of said first of said engagement elements and replacing it with another after a fixed number of treatments.

12. (Original) A method as in claim 11, wherein said fixed number is one.

13-15. (Canceled)

16. (Previously Presented) A system as in claim 1, wherein the alignment member includes a raised portion of the blood treatment device.

17. (Currently Amended) A system as in claim 1, wherein the support member includes a pair of rails.

18. (Currently Amended) A system as in claim 1, wherein the support member includes a pair of rails that support a part of the blood treatment device that carries a subset of the separate engagement elements.

19. (Currently Amended) A system as in claim 1, wherein the support member includes a pair of rails that support a part of the blood treatment device that carries a subset

of the separate engagement elements, the part of the blood treatment device including a door with a control panel thereon.

20. (Currently Amended) A renal replacement therapy system, comprising:

a blood treatment device with at least one actuator peristaltic pump;

a cartridge with a fluid circuit supported thereby, the fluid circuit being engageable with the at least one actuator peristaltic pump mechanism;

the blood treatment device including engagement elements that are brought into engagement with the fluid circuit portions by moving a first of the engagement elements toward a second of the engagement elements;

the blood treatment device having a support member configured to extend between the engagement elements such that a first end portion of the support member is attached to the first engagement element and a second end portion of the support member is attached to the second engagement element, and further configured to permit the cartridge to rest thereon, the blood treatment device further comprising ~~and an alignment member shaped to align the cartridge with the at least one actuator peristaltic pump mechanism when the cartridge is moved horizontally, the support member and the alignment member being such that a single vertical motion to rest the cartridge on the support member followed by a single horizontal motion of the cartridge to engage the alignment member positions the cartridge such that the separate engagement elements are may be brought together around the respective portions to engage the at least one actuator peristaltic pump mechanism.~~

21. (Currently Amended) A system as in claim 20, wherein the alignment member includes a raised portion of the blood treatment device.

22. (Currently Amended) A system as in claim 20 +8, wherein the support member includes a pair of rails.

23. (Currently Amended) A system as in claim 20 +8, wherein the support member includes a pair of rails that support a part of the blood treatment device that carries a subset of the separate engagement elements.

24. (Currently Amended) A system as in claim 20 +8, wherein the support member includes a pair of rails that support a part of the blood treatment device that carries a subset of the separate engagement elements, the part of the blood treatment device including a door with a control panel thereon.

25. (Currently Amended) A system as in claim 20 +8, wherein the support member includes a horizontal member.

26. (Currently Amended) A system as in claim 20 +8, wherein the first engagement element moves relative to the second engagement element on a pair of rails, the support member including at least one of the pair of rails.

27. (Currently Amended) A system as in claim 20 +8, wherein the first engagement element moves relative to the second engagement element on a pair of rails, the support member including at least one of the pair of rails, the first engagement

element being fixed and the second engagement element being movable, the first engagement element carrying a control panel.

28. (Currently Amended) A method of performing renal replacement therapy using a therapy machine including at least one pump race, at least one pump roller, an alignment member, and a fluid circuit with at least two tubes, comprising:

moving the fluid circuit horizontally on a support member configured to extend between a first engagement element which includes the at least one pump race and a second engagement element which includes the at least one pump roller toward the alignment member until the fluid circuit is engaged by the alignment member restricting the movement of the at least two tubes and causing the at least two tubes to be in alignment with the at least one pump roller;

moving the at least one pump roller and the at least one pump race in mutually horizontal directions on the support member and urging them together to engage and pinch the at least two tubes between the at least one pump roller and the at least one pump race;

operating the at least one pump roller to convey blood through one of the at least two tubes and to convey at least one non-blood fluid through another of the at least two tubes.

29. (Currently Amended) The method of claim 28, further comprising providing the fluid circuit in a cartridge and resting the cartridge on the a-support member prior to moving the fluid circuit horizontally toward the alignment member.